

APPLICATION

FOR

UNITED STATES LETTERS PATENT

TITLE: **TEMPERATURE TUNED ARRAYED
WAVEGUIDE GRATING**

INVENTORS: **Mahesh R. Junnarkar and
Anirban Bandyopadhyay**

Express Mail No. EV 337 932 533 US

Date: September 24, 2003

TEMPERATURE TUNED ARRAYED WAVEGUIDE GRATING

Background

This invention relates generally to arrayed waveguide gratings.

With wavelength division multiplexed optical signals,
5 a plurality of different optical signals, each having a
different wavelength, may be multiplexed over the same
optical link. At intended destinations, one or more of the
wavelength signals may be separated using a demultiplexing
technique.

10 An arrayed waveguide grating, also called a phased
arrayed waveguide or phaser, works like a diffraction
grating. It may be fabricated as a planar structure
including input and output waveguides, input and output
slab waveguides, and arrayed waveguides. The length of any
15 arrayed waveguide may differ from adjacent waveguides by
constant ΔL .

The input slab waveguide splits the wavelength
channels among the arrayed waveguides. Each portion of the
input light traveling through the arrayed waveguide
20 includes all the wavelengths that have entered the grating.
Each wavelength in turn is individually phase shifted. As
a result of that phase shift and phase shifts at the
input/output slab waveguides, every portion of the light at
a given wavelength acquires different phase shifts. These

portions may interfere at the output slab waveguide,
producing a set of maximum light intensities. The
direction of each maximum light intensity depends on its
wavelength. Thus, each wavelength is directed to an
5 individual output waveguide.

Wavelength tuning an arrayed waveguide grating is done
by heating or cooling the grating. The amount of
temperature tuning is proportional to the mismatch between
the design and the result of a particular set of process
10 conditions. The final temperature may even be outside a
range specified by the customer. The final temperature may
also affect the thermal budget, especially in integrated
components like variable optical attenuators, multiplexers,
and optical add-drop multiplexers, to mention a few
15 examples.

Targeting the central wavelength of an interferometer
with small free spectral range demands extremely low
process variation across the wafer, as well as from wafer
to wafer. This is particularly important for arrayed
20 waveguide grating-based interferometers. Any deviation of
the central wavelength affects bandwidth, polarization
dependent losses, and cross talk of the arrayed waveguide
grating.

Existing techniques of compensating the process
25 dependence of the arrayed waveguide grating offer
relatively coarse tunability. For example, the use of

multiple input waveguides with a vernier spacing and extra output waveguides to receive light with correct wavelengths has been utilized. Temperature tuning may also be done using a heater or a thermo-electric cooler to tune the refractive index of the entire array of arrayed waveguides.

Thus, there is a need for better ways to tune arrayed waveguide gratings.

Brief Description of the Drawings

Figure 1 is a top plan view of one embodiment of the present invention; and

Figure 2 is a partial, bottom plan view of the embodiment shown in Figure 1 in accordance with one embodiment of the present invention.

Detailed Description

Referring to Figure 1, the planar light wave circuit 10 may include an arrayed waveguide grating. An input waveguide 12a is coupled to an input slab waveguide 14a. The output waveguides 12b are coupled to an output slab waveguide 14b. A slab waveguide, also called a free propagation region, confines light in one dimension, usually the vertical dimension, and does not significantly confine the light in another dimension, typically the horizontal direction, such as the plane of the circuit 10.

Between the slab waveguides 14a and 14b are an array of arrayed waveguides 16. Generally, a large number of

such arrayed waveguides may be provided, each of which differ in length by the amount ΔL from an adjacent waveguide. Waveguides 16 may be located on the top side 20 of the planar light wave circuit 10. On the opposite or back side 22, generally aligned with the waveguide 16, are a plurality of heaters 18. Generally the heaters 18 extend in substantially the same physical arrangement as the arrayed waveguides 16. In one embodiment, there may be less heaters 18 than arrayed waveguides 16. Adjacent heaters 18 may generate a temperature gradient across intervening, overlying waveguides 16.

Referring to Figure 2, on the back side 22 of the planar light wave circuit 10, may be a plurality of heaters 18. Each heater 18 may be coupled to a pad 24 in one embodiment. A pad 24 in turn may be coupled to a fusable link 26 in one embodiment. In one embodiment, the fusable links 26 may be laser openable, fusable links. A fusable link 26 may be selectively connectable to an off die power supply 28 in one embodiment. Thus, if the fusable link 26 is open, the coupled heater 18 is not operated. If the fusable link 26 is closed (or not opened by exposure to a laser beam), the particular heater 18 may be operated by the power supply 28 to create a temperature gradient on the top side 20 of the circuit 10.

Thus, in one embodiment of the present invention, temperature gradient assisted wavelength tuning may be

utilized. A local temperature gradient may be artificially created across the array of waveguides 16. For example, one can tune 150 pm with a transverse gradient of 1°C per millimeter on top of 12.5 pm/°C tuning provided by the
5 overall heating. The heaters 18 used for this purpose may have the capability of selectively heating filaments to generate the required gradient.

Thus, by customizing the heaters 18 through operation of the fusable links 26, one can use correct heater
10 elements to provide average base temperatures required by an end user, while adjusting the activated heater's placement on the backside 22 of the circuit 10 to provide fine tuning. The impact of the temperature gradient on crosstalk and bandwidth may be negligible in some
15 embodiments.

While the present invention has been described with respect to a limited number of embodiments, those skilled in the art will appreciate numerous modifications and variations therefrom. It is intended that the appended
20 claims cover all such modifications and variations as fall within the true spirit and scope of this present invention.

What is claimed is: